

Skywire™ 3G EVDO





Product Brief

Part Numbers	Description
NL-SW-EVDO-V	Skywire™, CDMA EVDO,
	Verizon
NL-SW-EVDO-A	Skywire™, CDMA EVDO,
	AERIS

Add robust cellular connectivity to your M2M devices without the cost, delay, and hassle of federal and carrier certifications. Extensive experience in designing and building embedded product solutions makes the NimbeLink Skywire™ end-device certified modems the smallest on the market. Its U.FL ports ensures antenna flexibility. It complies with the XBee® standard interface and supports EVDO Rev. A communication, minimizing costs of hardware and network access. And Verizon's commitment to the CDMA network helps ensure long product life.

NimbeLink's Skywire modem is available with bundled data plans from leading cellular carriers. This product supports CDMA EVDO Rev. A and also integrates GPS and GLONASS receivers for worldwide positioning coverage. Other footprint compatible products support 1xRTT, GSM/GPRS and LTE, and like the current products will let you quickly, easily, and economically incorporate fully-compliant cellular connectivity into devices without having to apply for certification.

This module also supports antenna diversity to improve receive sensitivity and download speeds.

Take the complexity out of designing cellular M2M solutions.

NimbeLink. Smart. Simple. Cellular.

Features

- Industry's smallest
- 2 U.FL port for antenna diversity
- 1 U.FL for GPS & GLONASS
- XBee® interface standard

Advantages

- FCC & Verizon OD Certified
- Supports GPS & GLONASS
- Migration path to 1xRTT, GSM & LTE
- Bundled data plans available



Technical Specifications

NL-SW-EVDO

Form Factor	
	Skywire™, XBee® Standard Interface
	29mm x 33mm x 10.5mm
Approvals	
	Regulatory: FCC
	Carrier: Verizon, AERIS
Speeds	
	3.1Mbps Download
	1.8Mbps Upload
Current Consumption	
	Input voltage: 3.5V-4.3Vdc
	I/O voltage: 1.65V-5.5Vdc
	Sleep mode: 15uA
	Normal: 3mA
	Active call: 750mA
Temperature Range	
	Operating and storage temperature -40C to +85
Antenna Specifications	
	U.FL primary and diversity
Support and Warranty	
	1 Year standard warranty



Contact a NimbeLink Sales Professional

612-285-3433

Email Us

www.NimbeLink.com/contact-us

Online

www.NimbeLink.com